

CITIZEN

Miyano

BNA42MSY

Fixed Headstock Type CNC Automatic Lathe








MSY

Configured with two spindles and one turret and equipped with a Y axis and X2 axis, the BNA42MSY is able to handle complex machining, with short cycle times and fast set ups.

The X2 axis to sub-spindle enables simultaneous independent machining of the front and back of the workpiece. This, in effect, provides the benefits of a twin turret machine with the significant cost savings of a single turret model.

- 2 tool simultaneous cutting
- renowned Miyano accuracy
- quick to set up and changeover
- highly efficient for small and medium batch sizes (lots)
- compact design for improved floor space efficiency






Cycle time shortened by superimposition control

A turret incorporating X, Y and Z axes (HD1) and a sub spindle incorporating X and Z axes (SP2) open up the possibility of machining by superimposition control, where the sub spindle synchronizes with the turret to machine a workpiece in the main spindle (SP1), a very effective way to shorten cycle time.

High-rigidity spindle


To achieve powerful cutting, the spindle, which is the key component in machining, is equipped with angular contact ball bearings at the front and double-row cylindrical roller bearings at the rear.



Spindle Motors with Increased Output


The spindle 1 motor has the highest output in the BNA series. This enables powerful cutting.

Motor pulley diameter: $\phi 125\text{mm}$ Moto $r(\text{min}^{-1})$ 1500 2000 4500 7632
 Speed-reduction rate: 0.786
 Spindle pulley diameter: $\phi 159\text{mm}$ Spindle (min^{-1}) 1179 1572 3537 6000




Basic Construction

High-rigidity scraped slideways are used on all axes. These slideways with face contacts have exceptional rigidity and damping characteristics, achieve powerful cutting, and help to prolong cutting tool life.



Substantial Reduction in Non-cutting Time

The unique control system cuts non-cutting time by 27% (compared to earlier equivalent Miyano products). The result is a 13% reduction in cycle time.




Easy to Use Tooling System

The turret has 8 stations, but the half-indexing mechanism makes it possible to mount tools at up to 16 positions. The use of optional multiple tool holders can further increase the number of tool positions.



Support Screens Improve Operating Convenience



The program screen, organized for easy reading, can be displayed in synchronization with the editing screen. This simplifies the editing of complex programs with a lot of queuing.

All you have to do is input the machining length, chucking length and so on, and the escape and approach positions are automatically calculated. This is useful for collision prevention and shortening setup times.





HMI (Human Machine Interface) Adopted

Graphics displayed for each item and screens that display all the necessary information in one place greatly improve operating convenience.





The function displays the list of G and M codes including explanations of the arguments to support programming.




The coordinate calculation function and calculator function incorporated in the NC unit can be used for complex intersection point calculations.

Programs for canned cycles etc. can be created in the conversational style.


External view



Tooling area



Tooling system



Machine specification

Items		BNA-42MSY2
Machining capacity		
Max. machining diameter of bar work	SP1	42 mm Dia.
	SP2	34 mm Dia.
Max. work length		100 mm
Slide stroke		
Turret slide stroke	X1 axis	140 mm
	Z1 axis	235 mm
	Y1 axis	70 (±35 mm)
Spindle slide stroke	X2 axis	140 mm
	Z2 axis	310 mm
Spindle		
Number of spindle		2
Inner diameter of draw tube	SP1	43 mm Dia.
	SP2	30 mm Dia.
Spindle speed range	SP1	6,000 min ⁻¹
	SP2	5,000 min ⁻¹
Collet chuck type	SP1	Hardinge S20, DIN 173E, B&S 22D, HAINBUCH SK42
	SP2	Spring collet, DIN171E, B&S 22
Power chuck type		5"thru-hole chuck
Spindle minimum index angle	SP1	0.001°
	SP2	0.001°
Turret		
Number of turret		1
Type of turret		8st.
Shank size of turning tool		20 mm squ.
Diameter of sleeve holder		25mm Dia.
Revolving tools		
Number of revolving tools		Max. 8
Tool spindle speed range		Max. 6,000min ⁻¹
Machining capacity	Drill	Max.10 mm Dia.
	Tap	Max. M8×1.25
Feed rate		
Rapid Feed rate	X1 axis	20 m/ min
	Z1 axis	20 m/ min
	Y1 axis	12 m/ min
	X2 axis	12 m/ min
	Z2 axis	20 m /min
Motors		
Spindle drive	SP1	11/ 7.5kw (15min/ cont.)
	SP2	5.5/ 3.7kw (15min/ cont.)
Revolving tool drive		1.0 kW
Power supply		
Electrical capacity		29 KVA
Coolant tank capacity		165 L
Machine dimensions		
Machine height		1,620 mm
Floor space		W 2,278 × D 1,450 mm
Machine weight		3,000 kg
Optional accessories		
Spindle air blow, Spindle Brake, High pressure coolant, Inner High pressure coolant & Air blow, Coolant level swich, Signal tower, Coolant mist collector, Automatic fire- extinguishing equipment, Automatic power shut-off, Chip conveyor, Chip box, Parts catcher, Parts conveyor, Drill breakage detector, RS-232C, 100V		

NC Specification	
Model device	MITSUBISHI M70V
Display devise	8.4"color LCD
Controllable axis	
command specified axes	X1, Z1, Y1, C1, X2, Z2, C2-axis
auxiliary axes	C3, T1-axis
Control axis groups	Two groups
Input code	ISO
Command input system	Incremental and absolute
Feed command system	Per rotation feed and per minute
Cutting Feed Rate Override	Max.100%
Tool offset data	80 pairs
Program storage capacity	160m
Standard function	
On machine program check function	
Manual feed function	
Manual data input (MDI) function	
Operation time display	
Product counter display	
Cycle time check function	
Preparation functions	
Start position automatic return	
Automatic cut-off machining function	
Tool set function	
Spindle speed simultaneous command for 3 spindle	
3 Sets of M code simultaneous command	
Control axis swap function	
Control axes superimpose command	
Arbitrary superposition function	
Function to superimpose 2 pairs of axes	
BNA-42MSY dedicated macros	
Background editing	
Simultaneous program editing two control axis group	
Editing support functions	
Calculator function	
Code list display	
Coordinate calculation function	
Main spindle C-axis function spindle	
Constant surface speed control	
Cut off confirmation	
Tool nose R compensation function	
Arc radius specification	
Thread cutting canned cycle	
Spindle synchronizing control function	
Milling interpolation	
Option	
Helical interpolation, Corner chamfering/ Radius function,	
Spindle synchronous tap function, Revolving tool synchronous tap function,	
Custom macro, Multiple canned cycles for turning, Canned cycles for drilling,	
Inchi/ metric change	

CITIZEN MACHINERY CO., LTD.

	JAPAN	CITIZEN MACHINERY CO.,LTD. 4107-6 Miyota, Miyota-machi, Kitasaku-gun, Nagano-ken, 389-0206, JAPAN	TEL.81-267-32-5901	FAX.81-267-32-5908
	SOUTH ASIA / KOREA	CITIZEN MACHINERY CO.,LTD. 4107-6 Miyota, Miyota-machi, Kitasaku-gun, Nagano-ken, 389-0206, JAPAN	TEL.81-267-32-5916	FAX.81-267-32-5928
	TAIWAN	CINCOM MIYANO TAIWAN CO.,LTD. 10FL, No.174, Fuh Sing N. Rd., Taipei, TAIWAN	TEL.886-2-2715-0598	FAX.886-2-2718-3133
	CHINA	CITIZEN (CHINA) PRECISION MACHINERY CO.,LTD. 10058, XINHUA ROAD OF ZHOUCUN, ZIBO, SHANDONG, P.R. CHINA	TEL.86-533-6150560	FAX.86-533-6161379
	EUROPE-Germany	CITIZEN MACHINERY EUROPE GmbH Mettinger Strasse 11, D-73728 Esslingen, GERMANY	TEL.49-711-3906-100	FAX.49-711-3906-106
	EUROPE-UK	CITIZEN MACHINERY UK LTD 1 Park Avenue, Bushey, WD23 2DA, UK	TEL.44-1923-691500	FAX.44-1923-691599
	EUROPE-Italia	CITIZEN MACCHINE ITALIA s.r.l. Via Campo Romano 11/13 - 24050 Spirano (BG), ITALY	TEL.39-035-877738	FAX.39-035-876547
	AMERICA	MARUBENI CITIZEN-CINCOM INC. 40 Boroline Road Allendale, NJ 07401, U.S.A.	TEL.1-201-818-0100	FAX.1-201-818-1877

All specifications are subject to change without prior notice. This product is an export control item subject to the foreign exchange and foreign trade act. Thus, before exporting this product, or taking it overseas, contact your CITIZEN machine dealer. Please inform your CITIZEN machine dealer in advance of your intention to re-sell, export or relocate this product. For the avoidance of doubt products includes whole or part, replica or copy, technologies and software. In the event of export, proof of approval to export by government or regulatory authority must be evidenced to CITIZEN. You can operate the machines after the confirmation of CITIZEN. CITIZEN is a registered trademark of Citizen Watch Co., Japan.