

CITIZEN

Miyano

LX08c

CNC Lathe







We proudly introduce an 8-inch chucking machine, developed through and close study of the basic performance required of machine tools.

The rigid turret uses precision scraped square guideways providing excellent vibration damping characteristics, the rigid spindle is supported by double-row cylindrical roller bearings and angular contact ball bearings, and the heavy 30° slanted bed is in a platform-like surface table where the turret and the spindle are mounted.

The high levels of basic performance accomplished give consistently high machining accuracy.



Rigid Base



Heavy Bed, the Basis for the Machine's High Performance


The 30° slanted bed, which is cast in one piece, provides outstanding thermal stability thanks to smooth chip flow to minimize dimensional changes during machining, and supports high-precision machining as a closed-structure rigid body.

Reliable Flat Faces to Mount Major Machine Units

The flat faces of the 30° slanted bed where major machine units such as spindles and tool slides are mounted assure rigidity by adopting the platform-like surface table.

This structure maintains stable flatness in the face of external and internal factors that work to impair machining accuracy, minimizing changes in relative dislocation between the workpiece and tool nose.

Turret



Highly Rigid Turret


For the turret, subject to cutting forces and vibration under severe conditions, precision scraped square guideways are used on all axes to increase rigidity and vibration damping characteristics.

A two-piece curvic coupling is used to clamp the turret, prioritizing rigidity. This also realizes a compact mechanical structure.

Heavy Cutting by Direct Mounting of Tools

Since 25-mm square tools can be directly mounted on the turret, tools can be clamped securely with a short overhang, enabling heavy cutting.

Spindle



Rigid 8-inch Spindle

The spindles manufactured in the dedicated in-house production lines feature rigid double-row cylindrical roller bearings and angular contact ball bearings to support the spindle at the front and rear. By spacing them sufficiently far apart, the bearable moment load and straightness of the center of rotary axis are improved.

Hard Turning



From Grinding to Hard Turning

Hard turning is a kind of turning process for machining quenched materials on an NC lathe using CBN or ceramic tools.

Advantages of hard turning over grinding

Initial investment cost (machine price) is low.


Several grinding processes can be integrated into turning processes performed on a single NC lathe.

Since all machining processes including outer and inner turning, circular machining and free-form surface machining can be performed in one chucking, geometrical accuracy, such as straightness, squareness and concentricity, is considerably improved.


Cycle time can be reduced thanks to short loading and unloading time.

Dry cutting is environmentally friendly - reduced use of coolant, and recovery of resources by recycling chips instead of disposing of the sludge generated in grinding.

Examples of circular and free-form surface machining



Machining accuracy in hard turning



NC Custom menu

The functions convenient for machining and checking can be called in one-touch operations.




CUSTOM MENU

Displays the list of custom screens.



BLOCK SKIP

Used to set block skip 1 to block skip 9.



TOOL COUNTER

Used to set and reset the tool counter stop value and enter the tool wear offsets.



CYCLE TIME

Measures the cutting time, non-cutting time and running time in each cycle.



AUTOMATIC RUNNING MONITOR

Displays the control status of each axis. Used to set ON / OFF for the machine lock function.




START CONDITION

Used to set the start conditions for automatic running.



SPINDLE & RVT

Used to set the rotational speed of the spindle and revolving tools. Used to set the spindle override.



MAINTENANCE

Used to set ON / OFF for the maintenance items. Used to set ON / OFF for turret zero point adjustment.



TURRET MAINTENANCE

Used to adjust the turret zero point.



MANUAL OPERATION



Displays the zero point lamp status and the machine coordinate of each axis.




OPTION DEVICE

Used to select an auxiliary device such as a part catcher to be operated manually.


External view



Tooling area



Tooling system



Machine specifications

Items	LX-08C	
Machining capacity		
Max. work length	320mm	
Max. machining diameter	Max. 210mm Dia.	
Spindle		
Number of spindle	1	
Spindle speed range	40 - 4,000min ⁻¹	
Spindle draw tube dia.	52mm Dia.	
Type of chucking system	Hydraulic thru-hole chuck cylinder	
Collet chuck type	HardingeS22 with pad	
Power chuck type	8" thru-hole power chuck	
Tool slide		
Number of Tool slide	1	
Type of tool slide	10st. turret	
Size of Turning Tools	25mm Sq.	
Size of Drill & Boring Tools	40mm Dia.	
Turret Index Time	0.26 sec./ 1pos.	
Slide		
Slide travel	X-axis	175 mm
	Z-axis	435 mm
Rapid Feed rate	X-axis	12 m/ min.
	Z-axis	16 m/ min.
Tailstock (Option)		
Slide type	Hydraulic	
Max. slide travel	300 mm	
Live center size	MT4	
Max. slide thrust	4.3 KN/ 3.4 MPa	
Min. slide thrust	0.36 KN/ 0.3 MPa	
Quill type	Hydraulic	
Max. slide travel	Quill 90 mm + Manyual 220 mm	
Live center size	MT4	
Max. slide thrust	4.3KN /3.4 MPa	
Min. slide thrust	0.36KN /0.3 MPa	
Tank capacity		
Hydraulic oil tank capacity	10 L	
Lubricating oil tank capacity	2 L	
Coolant tank capacity	150 L	
Machine dimensions		
Machine hight	1,734 mm	
Floor space	2,150 mm × 1,728 mm	
Machine weight	4,500 kg	
Motors		
Spindle drive	AC 75/ 11	
Coolant ponp	AC 0.18 kW	
Power supply		
Voltage	AC 200 V ± 10%, 50/ 60 Hz± 1%	
Capacity	22 KVA	
Air supply	0.5 MPa (5 kgf/ cm ²)	
Fuse	100 A	
Others		
Splash guard interlock, Foot switch		
Option		
Collet system, Power chuck system, Pneumatic Unit,Chuck air blow, Spindle inner air blow		
Automatic fire-extinguishing equipment, Automatic power shut-off, Parts catcher, Parts conveyor		
High pressure coolant, Tail stock, Chip conveyor, Chip box, Total & preset counte		
Coolant mistcollector, Oil mist damper Warning light, 1100V, RS-232C, etc.		

[illegible]

CITIZEN MACHINERY CO., LTD.

CITIZEN	JAPAN	CITIZEN MACHINERY CO.,LTD. 4107-6 Miyota, Miyota-machi, Kitasaku-gun, Nagano-ken, 389-0206, JAPAN	TEL.81-267-32-5901	FAX.81-267-32-5908
	SOUTH ASIA / KOREA	CITIZEN MACHINERY CO.,LTD. 4107-6 Miyota, Miyota-machi, Kitasaku-gun, Nagano-ken, 389-0206, JAPAN	TEL.81-267-32-5916	FAX.81-267-32-5928
	TAIWAN	CINCOM MIYANO TAIWAN CO.,LTD. 10FL, No.174, Fuh Sing N. Rd., Taipei, TAIWAN	TEL.886-2-2715-0598	FAX.886-2-2718-3133
	CHINA	CITIZEN (CHINA) PRECISION MACHINERY CO.,LTD. 10058, XINHUA ROAD OF ZHOUCUN, ZIBO, SHANDONG, P.R. CHINA	TEL.86-533-6150560	FAX.86-533-6161379
	EUROPE-Germany	CITIZEN MACHINERY EUROPE GmbH Mettinger Strasse 11, D-73728 Esslingen, GERMANY	TEL.49-711-3906-100	FAX.49-711-3906-106
	EUROPE-UK	CITIZEN MACHINERY UK LTD 1 Park Avenue, Bushey, WD23 2DA, UK	TEL.44-1923-691500	FAX.44-1923-691599
	EUROPE-Italia	CITIZEN MACCHINE ITALIA s.r.l. Via Campo Romano 11/13 - 24050 Spirano (BG), ITALY	TEL.39-035-877738	FAX.39-035-876547
	AMERICA	MARUBENI CITIZEN-CINCOM INC. 40 Boroline Road Allendale, NJ 07401, U.S.A.	TEL.1-201-818-0100	FAX.1-201-818-1877

URL:<http://cmj.citizen.co.jp/>

All specifications are subject to change without prior notice. This product is an export control item subject to the foreign exchange and foreign trade act. Thus, before exporting this product, or taking it overseas, contact your CITIZEN machine dealer. Please inform your CITIZEN machine dealer in advance of your intention to re-sell, export or relocate this product. For the avoidance of doubt products includes whole or part, replica or copy, technologies and software. In the event of export, proof of approval to export by government or regulatory authority must be evidenced to CITIZEN. You can operate the machines after the confirmation of CITIZEN.

PRINTED IN JAPAN JULY 2016